

500 SERIES

and Model 680SS

- Oil-Fired or LP-Fired
- 115V/1PH
- 1725 RPM Direct-Drive Pump
- 7-Year Pump Warranty



Model 555SS (Shown with optional hose reel)



Model 558-Propane (Shown with optional Portagear & Propane Tank)



Model 560SS (Shown with optional hose reel)



Model 680SS

The **500 Series** delivers rugged, yet affordable, cleaning power for a broad range of applications, from agriculture to building maintenance. The sporty 555SS, with its stainless steel coil skin, is our most popular entry level hot water model—compact, evenly balanced, easy to maneuver, and engineered with the operator in mind. As with the entire Hotsy line, all models in the 500 series are ETL safety certified to UL-1776, with Hotsy pumps backed by a 7-year limited warranty. A pressure switch is standard on all 500 Series models. Equipped with a 50' hose.

MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	AMP	FUEL	BTU/HR	PUMP MODEL	PORTABILITY	DIMENSIONS	SHIP WT (lbs)
555SS	1.109-033.0	2.2	1300	2	115/1	20	Oil	214,300	Duplex - HHC165L.1	Std	33"Lx27"Wx41.5"H	360
558	1.109-610.0	2.2	1300	2	115/1	18	LP	227,000	Duplex - HHC165L.1	Optional	31.5"Lx26"Wx41"H	350
560SS	1.109-034.0	2.1	1500	2.3	115/1	20	Oil	214,300	Triplex - HHC205L.1	Std	33"Lx26"Wx44"H	395
680SS	1.109-035.0	3.0	1000	2	115/1	20	Oil	289,900	Triplex - HHC235R.1	Std	33"Lx27"Wx45.5"H	405

SS=Stainless Steel

OPTIONS

PART NO.	DESCRIPTION
8.717-728.0	8" LP Gas-Fired Draft Diverter, Model 558
8.717-764.0	8" Oil-Fired Draft Dampener, Models 555SS/560SS/680SS
8.903-049.0	Portagear, Model 558

OPTIONS

PART NO.	DESCRIPTION
8.717-791.0	Propane Tank, 43 lb.
8.903-034.0	Float Tank, 555SS (Field Install)
8.750-486.0	360° Pivot Reel, 100' (fits all 500 Series EXCEPT 558)

700 SERIES

and Model 895SS

- Oil-Fired, LP- or Natural-Gas-Fired
- 7-Year Pump Warranty
- Direct- & Belt-Drive



Model 790SS



Model 771-Propane (Shown with optional Portagear & Propane Tank)



Model 895SS

The **700 Series** offers a nice balance of Hotsy ruggedness and cleaning performance, yet the affordability of an entry-level machine. In addition to the two direct-drive models, this series also offers belt-drive models that clean at 3.5 GPM and 2000 PSI. More powerful yet is the new 895SS. The multiple fuel and electrical options makes the 700 series ideal for meeting the needs of commercial customers. All models are ETL safety certified and feature the Hotsy Triplex pump with a 7-year warranty. A pressure switch is standard on all 700 Series models. Equipped with a 50' hose.

MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	DRIVE	PORTABILITY	DIMENSIONS	SHIP WT (lbs)
771	1.109-611.0	3.0	1500	3	230/1	13	LP	280,000	HHC235R.1	Direct	Optional	32"Lx27"Wx45.5"H	415
772	1.109-037.0	3.0	1500	3	230/1	13	NG	338,000	HHC235R.1	Direct	N/A	32"Lx27"Wx45.5"H	415
790SS	1.109-612.0	3.0	2000	4TEFC	230/1	20	Oil	289,900	HHC340R.1	Belt	Std	37"Lx28"Wx45.5"H	450
795SS	1.109-039.0	3.5	2000	5	230/1	24	Oil	289,900	HHC340R.1	Belt	Std	37"Lx28"Wx45.5"H	455
795SS-208	1.109-040.0	3.5	2000	5	208/1	27	Oil	289,900	HHC340R.1	Belt	Std	37"Lx28"Wx45.5"H	500
895SS	1.109-077.0	3.5	3000	8.2	230/1	36	Oil	289,900	HHC506R.1	Belt	Std	37"Lx28"Wx45.5"H	480

SS=Stainless Steel

OPTIONS

PART NO.	DESCRIPTION
8.717-728.0	8" Natural Gas- or LP Gas-Fired Draft Diverter, Models 771/772
8.717-764.0	8" Oil-Fired Draft Dampener, Models 790SS, 795SS & 895SS
8.903-049.0	Portagear, Model 771
8.717-791.0	Propane Tank, 43 lb.

OPTIONS

PART NO.	DESCRIPTION
8.750-486.0	360° Pivot Reel, 100'
8.750-483.0	360° Pivot Reel, 200' (Hose Reels fit all 700 Series Models EXCEPT 771/ 772)

800 SERIES

- Oil-Fired
- Big & Beefy, Yet Easy To Maneuver
- Rugged Hotsy Pump with 7-Year Warranty
- Stainless-Steel Coil Skin



Shown with optional hose reel

The new 800 Series - rugged design, easy maneuverability and massive cleaning power. Comparable to the cleaning power of Hotsy's heavy-duty stationary units, the big and beefy 800 Series is surprisingly easy to maneuver into place, allowing you to tackle the heaviest of industrial cleaning jobs. The 28" wide wheel base helps with stability, yet is narrow enough to fit easily through doorways. Components are protected by an easy-to-remove cover allowing servicing access. All 800 series hot water pressure washers are backed by a 7-year warranty on the Hotsy Triplex pump. A pressure relief valve, upstream detergent injector and stainless steel coil wrap are standard features on all 800 Series models, which are ETL certified. Equipped with a 50' hose.



MODEL	PART NO.	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	DRIVE	PORTABILITY	DIMENSIONS	SHIP WT (lbs)
821	1.109-120.0	4.0	2300	6.2	3450	208/1	33	Oil	342,900	HHC506R.2	Belt	Std	51"Lx28"Wx51"H	632
842	1.109-121.0	4.0	2000	5	1725	208/3	20	Oil	342,900	HH406R.2	Belt	Std	51"Lx28"Wx51"H	622
843	1.109-122.0	4.0	2000	5	1725	230/1	29	Oil	342,900	HH406R.2	Belt	Std	51"Lx28"Wx51"H	622
844	1.109-123.0	4.0	2000	5	1725	230/3	19	Oil	342,900	HH406R.2	Belt	Std	51"Lx28"Wx51"H	622
845	1.109-124.0	4.0	2000	5	1725	460/3	10	Oil	342,900	HH406R.2	Belt	Std	51"Lx28"Wx51"H	691
851	1.109-125.0	4.0	3000	8.2	3450	208/1	44	Oil	342,900	HHC506R.2	Belt	Std	51"Lx28"Wx51"H	675
852	1.109-126.0	4.0	3000	7.5	1725	208/3	25	Oil	342,900	HH406R.2	Belt	Std	51"Lx28"Wx51"H	665
853	1.109-127.0	4.0	3000	7.5	1725	230/1	37	Oil	342,900	HH406R.2	Belt	Std	51"Lx28"Wx51"H	665
854	1.109-128.0	4.0	3000	7.5	1725	230/3	25	Oil	342,900	HH406R.2	Belt	Std	51"Lx28"Wx51"H	665
855	1.109-129.0	4.0	3000	7.5	1725	460/3	14	Oil	342,900	HH406R.2	Belt	Std	51"Lx28"Wx51"H	665
856	1.109-130.0	4.0	3000	8.2	3450	575/3	11	Oil	342,900	HHC506R.2	Belt	Std	51"Lx28"Wx51"H	680
873	1.109-131.0	5.0	3000	10	1725	230/1	42	Oil	395,452	HH406R.2	Belt	Std	51"Lx28"Wx51"H	670
874	1.109-132.0	5.0	3000	10	1770	230/3	29	Oil	395,452	HH406R.2	Belt	Std	51"Lx28"Wx51"H	675

OPTIONS

PART NO.	DESCRIPTION
8.930-170.0	Auto Start/Stop Kit (Field Installed)*
8.930-172.0	Thermal Shutdown Kit (Field Installed)
8.930-171.0*	Time Delay Shutdown (Field Installed)*
8.717-764.0	8" Oil-Fired Draft Dampener (Oil-fired models only)
8.750-486.0	360° Pivot Reel, 100'
8.750-483.0	360° Pivot Reel, 200'
8.916-989.0	Remote Station
8.711-907.0	Pneumatic Wheel - 12 1/2" (one wheel only)

* Note: Time Delay Shutdown and Auto Start/Stop cannot be combined on the same machine

900/1400 SERIES

- LP-or Natural Gas-Fired
- Belt-Drive Hotsy Pump
- Smart Relay Control provides control over run time, auto start/stop and shut down functionality
- Improved coil for greater temperature rise
- Remote Ready



The 900/1400 Series - 2013 brings new innovation to this flagship stationary model, now packed with more standard features! The most impressive upgrade is programmable smart control automation. Safety is key with a pressure relief valve and locking lid and side panels around the belt and pulleys to keep users safe. These electric-powered washers are available in either LP or Natural Gas fired models. New models have the same footprint as previous generations, so users can feel confident about upgrading. Panels may be easily removed for access to the machine components for servicing. All models are ETL certified to the rigid UL-1776 safety standards. Features a Hotsy highly efficient Triplex pump. Equipped with a 50' hose.



MODEL	PART NO.	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	DRIVE	DIMENSIONS	SHIP WT (lbs)
921N	1.109-691.0	4.0	2300	6.2	3450	208/1	28	NG	364,835	HHC506R.2	Belt	47.5"Lx21"Wx51"H*	700
926N	1.109-692.0	4.0	2000	5	1800	575/3	7	NG	364,835	HHC506R.2	Belt	47.5"Lx21"Wx51"H*	660
942P	1.109-693.0	4.0	2000	5	1725	208/3	18	LP	360,997	HH406R.2	Belt	47.5"Lx21"Wx51"H*	590
942N	1.109-694.0	4.0	2000	5	1725	208/3	18	NG	364,835	HH406R.2	Belt	47.5"Lx21"Wx51"H*	655
943P	1.109-695.0	4.0	2000	5	1725	230/1	25	LP	360,997	HH406R.2	Belt	47.5"Lx21"Wx51"H*	685
943N	1.109-696.0	4.0	2000	5	1725	230/1	25	NG	364,835	HH406R.2	Belt	47.5"Lx21"Wx51"H*	685
944P	1.109-697.0	4.0	2000	5	1725	230/3	16	LP	360,997	HH406R.2	Belt	47.5"Lx21"Wx51"H*	580
944N	1.109-698.0	4.0	2000	5	1725	230/3	16	NG	364,835	HH406R.2	Belt	47.5"Lx21"Wx51"H*	680
945P	1.109-699.0	4.0	2000	5	1725	460/3	8	LP	360,997	HH406R.2	Belt	47.5"Lx21"Wx51"H*	585
945N	1.109-700.0	4.0	2000	5	1725	460/3	8	NG	364,835	HH406R.2	Belt	47.5"Lx21"Wx51"H*	585
1451N	1.109-701.0	4.0	3000	8.2	3450	208/1	42	NG	364,835	HHC506R.2	Belt	47.5"Lx21"Wx51"H*	730
1452P	1.109-702.0	4.0	3000	7.5	1725	208/3	24	LP	360,997	HH406R.2	Belt	47.5"Lx21"Wx51"H*	625
1452N	1.109-703.0	4.0	3000	7.5	1725	208/3	24	NG	364,835	HH406R.2	Belt	47.5"Lx21"Wx51"H*	625
1453P	1.109-704.0	4.0	3000	7.5	1725	230/1	34	LP	360,997	HH406R.2	Belt	47.5"Lx21"Wx51"H*	735
1453N	1.109-705.0	4.0	3000	7.5	1725	230/1	34	NG	364,835	HH406R.2	Belt	47.5"Lx21"Wx51"H*	735
1454P	1.109-706.0	4.0	3000	7.5	1725	230/3	24	LP	360,997	HH406R.2	Belt	47.5"Lx21"Wx51"H*	625
1454N	1.109-707.0	4.0	3000	7.5	1725	230/3	24	NG	364,835	HH406R.2	Belt	47.5"Lx21"Wx51"H*	700
1455P	1.109-708.0	4.0	3000	7.5	1725	460/3	12	LP	360,997	HH406R.2	Belt	47.5"Lx21"Wx51"H*	630
1455N	1.109-709.0	4.0	3000	7.5	1725	460/3	12	NG	364,835	HH406R.2	Belt	47.5"Lx21"Wx51"H*	780
1456N	1.109-710.0	4.0	3000	8.2	3450	575/3	10	NG	364,835	HHC506R.2	Belt	47.5"Lx21"Wx51"H*	621
1473P	1.109-711.0	5.0	3000	10	1725	230/1	42	LP	378,617	HH406R.2	Belt	47.5"Lx21"Wx51"H*	735
1473N	1.109-713.0	5.0	3000	10	1725	230/1	42	NG	390,025	HH406R.2	Belt	47.5"Lx21"Wx51"H*	735
1474P	1.109-712.0	5.0	3000	10	1770	230/3	29	LP	378,617	HH406R.2	Belt	47.5"Lx21"Wx51"H*	740
1474N	1.109-714.0	5.0	3000	10	1770	230/3	29	NG	390,025	HH406R.2	Belt	47.5"Lx21"Wx51"H*	740

* including connectors and flue outlet

OPTIONS

PART NO.	DESCRIPTION
8.916-989.0	Remote Station
8.916-988.0	Soap Solenoid and Switch
8.903-079.0	LP Conversion-Series (Factory Installed)
8.717-728.0	8" Natural Gas- or LP Gas-Fired Draft Diverter (Gas-fired models only)

1800 SERIES



- Natural Gas, Oil or optional LP-Fired
- Belt Drive with 7-Year Warranty
- Smart Relay Control provides control over run time, auto start/stop and shut down functionality

The **1800 Series** provides stationary cleaning with hot water indoors. The 7 models are electric-powered and natural gas, oil or LP gas-heated, using Hotsy's high-efficiency vertical hot water coil. The coil skin comes standard with stainless steel. The sleek cabinet has removeable side and front panels, making it easy for routine preventative maintenance and service. The Smart Relay allows the washer to be customized to individual needs, and is protected behind the front panel. This heavy-duty cleaning machine is ideal for use in manufacturing or even food processing facilities where hot water is needed for cleaning machinery and equipment indoors. All models are certified to the rigid UL-1776 safety standards and feature the highly efficient Hotsy Triplex pump. A pressure switch is a standard feature on all 1800 Series models. Equipped with a 50' hose.



MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	DRIVE	DIMENSIONS	SHIP WT (lbs)
1812SS	1.109-660.0	6.0	2500	10	230/1	42	NG	558,050	HX9536L.2	Belt	51"Lx31"Wx53.25"H	1,020
1830SS	1.109-665.0	6.0	3000	15	230/3	35	Oil*	579,776	HX9536L.2	Belt	51"Lx31"Wx53.25"H	1,020
1832SS	1.109-662.0	6.0	3000	15	230/3	33	NG	558,050	HX9536L.2	Belt	51"Lx31"Wx53.25"H	1,020
1832SS-208	1.109-661.0	6.0	3000	15	208/3	36	NG	558,050	HX9536L.2	Belt	51"Lx31"Wx53.25"H	1,020
1833SS	1.109-666.0	6.0	3000	15	460/3	21	Oil*	579,776	HX9536L.2	Belt	51"Lx31"Wx53.25"H	1,020
1835SS	1.109-663.0	6.0	3000	15	460/3	19	NG	558,050	HX9536L.2	Belt	51"Lx31"Wx53.25"H	1,020
1836SS	1.109-664.0	6.0	3000	15	575/3	16	NG	558,050	HX9536L.2	Belt	51"Lx31"Wx53.25"H	1,020

SS=Stainless Steel

*Oil-Fired models are not supplied with a fuel tank.

OPTIONS	
PART NO.	DESCRIPTION
8.916-989.0	Remote Station
8.916-988.0	Soap Solenoid and Switch

OPTIONS	
PART NO.	DESCRIPTION
8.903-074.0	LP Conversion Kit (Factory Installed)
9.801-040.0	10" Natural Gas or LP Gas Draft Diverter

5700/5800 SERIES



- Oil, Natural Gas or optional LP-Fired
- Belt Drive Pump with 7-Year Warranty
- Smart Relay Control provides control over run time, auto start/stop and shut down functionality

The **5700 and 5800 Series** produces a powerful punch and is ideal for wash bay installations. With its 20 HP Baldor motor driving the incomparable Hotsy Triplex Pump with NESTechnology with U-Seals and a vertical banded belt, the 5700 and 5800 Series delivers cleaning power up to 9.5 GPM and 3000 PSI. Completely redesigned with a sleek cabinet with removeable panels for easy access for maintenance. A removeable control panel provides access to the adjustable temperature control and the Smart Relay for secured control of operating positions. Remote ready for wash bay installations. All models are stationary and certified to the rigid UL-1776 safety standards. Equipped with a 50' hose.



MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	HOSE	SHIP WT
5730SS	1.109-658.0	8.0	3000	20	230/3	44	Oil*	768,000	HX9536L.2	50'	1,471
5732SS-208	1.109-654.0	8.0	3000	20	208/3	55	NG	720,450	HX9536L.2	50'	1,471
5732SS	1.109-655.0	8.0	3000	20	230/3	42	NG	720,450	HX9536L.2	50'	1,471
5733SS	1.109-659.0	8.0	3000	20	460/3	23	Oil*	768,000	HX9536L.2	50'	1,471
5735SS	1.109-656.0	8.0	3000	20	460/3	21	NG	720,450	HX9536L.2	50'	1,471
5736SS	1.109-657.0	8.0	3000	20	575/3	16	NG	720,450	HX9536L.2	50'	1,471
5832SS	1.109-651.0	9.5	2500	20	230/3	42	NG	939,890	HX1036L.2	50'	1,471
5832SS-208	1.109-650.0	9.5	2500	20	208/3	48	NG	939,890	HX1036L.2	50'	1,471
5835SS	1.109-652.0	9.5	2500	20	460/3	21	NG	939,890	HX1036L.2	50'	1,461
5836SS	1.109-653.0	9.5	2500	20	575/3	16	NG	939,890	HX1036L.2	50'	1,471

SS=Stainless Steel

Dimensions: 51"L x 31"W x 63.4"H

*Oil-Fired models are not supplied with a fuel tank.

OPTIONS	
PART NO.	DESCRIPTION
8.916-916.0	LP Conversion Kit, 5700 (Factory Installed)
8.916-915.0	LP Conversion Kit, 5800 (Factory Installed)

OPTIONS	
PART NO.	DESCRIPTION
8.916-989.0	Remote Station
8.916-988.0	Soap Solenoid and Switch
8.717-730.0	12" Natural Gas or LP-Gas Draft Diverter

GAS-ENGINE SERIES

DIRECT-DRIVE

- Oil-Fired
- 12 Volt DC
- Direct Drive
- 3 Battery-less Models
- 2 Electric-Start Models
- 7-Year Pump Warranty



871SS



965SS



1065SSE

The Gas Engine Series consist of the most compact and portable hot water pressure washers on the market. Powered by reliable gasoline engines, all you need is water and you can clean anywhere anytime. The five models offer a broad range of cleaning power, from 2.7 to 3.8 GPM and from 2400 to 3500 PSI. All models feature Hotsy's highly efficient Triplex pump backed by Hotsy's 7-year pump warranty and all are ETL safety certified. All models are equipped with a standard pressure switch and 50' hose.



MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	BURNER	BTU/HR	PUMP MODEL	DRIVE	PORTABILITY	DIMENSIONS	SHIP WT (lbs)
871SS*	1.110-014.0	2.7	2400	Subaru EX21	211	12V DC	248,500	HG3030G.1	Direct	Std	43"Lx27"Wx39"H	400
965SS*	1.110-015.0	3.0	3000	Honda GX270	270	12V DC	248,500	HG3035G1.1	Direct	Std	47"Lx31"Wx41"H	445
1065SS*	1.110-010.0	3.5	3000	Honda GX340	389	12V DC	309,900	HS3540G.2	Direct	Std	47"Lx31"Wx45"H	495
1065SSE†	1.110-011.0	3.5	3000	Honda GX340	389	12V DC	309,900	HS3540G.2	Direct	Std	47"Lx31"Wx45"H	510
1075SSE†	1.110-012.0	3.8	3500	Honda GX340	389	12V DC	309,900	HS4040G.2	Direct	Std	47"Lx31"Wx45"H	520

*Battery not required †12V battery required, but not supplied E= Electric-start engine

GAS-ENGINE SERIES

BELT-DRIVE

- Oil-Fired
- 12 Volt DC
- Belt Drive
- 2 Electric-Start Models
- 7-Year Pump Warranty



1075BE (Shown with optional caster wheel kit)



965B (Shown with optional pneumatic tires)



1080BE (Shown with optional stainless steel coil wrap and skid rails)

The belt-drive versions of the Gas Engine Series provide versatility with the roll cage design. Designed to fit the needs of the end-user, this versatile hot water washer converts easily to a skid unit, portable with wheels or a wheel/caster kit, or can be mounted on a trailer. Powered by reliable gasoline engines, the three models offer a broad range of cleaning power, from 3.0 to 4.6 GPM and from 3000 to 3500 PSI. All models feature the Hotsy Triplex pump backed by Hotsy's 7-year pump warranty and all are ETL safety certified. All models are equipped with a standard pressure switch and 50' hose.



MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	BURNER	BTU/HR	PUMP MODEL	DRIVE	PORTABILITY	DIMENSIONS	SHIP WT (lbs)
965B*	1.110-565.0	3.0	3000	Honda GX270	270	12V DC	248,500	HD3030L.1	Belt	Optional	42"Lx27.5"Wx39"H	590
1075BE†	1.110-566.0	4.0	3500	Honda GX390	389	12V DC	385,800	HM4035L.3	Belt	Optional	42"Lx27.5"Wx39"H	625
1080BE†	1.110-567.0	4.6	3500	Briggs VAN 16	479	12V DC	385,800	HM4035L.3	Belt	Optional	42"Lx27.5"Wx39"H	665

*Battery not required †12V battery required, but not supplied E= Electric-start engine B= Belt Drive

OPTIONS

PART NO.	DESCRIPTION
8.916-172.0	Float Tank Kit (includes high pressure detergent kit), 1075BE & 1080BE models
8.916-173.0	Float Tank Kit (includes high pressure detergent kit) 965B model
8.931-259.0	Skid Rail Kit (Field Installed)- adds 3.875" to height
8.931-260.0	Caster Kit - 2 casters / 2 wheels (Field Installed) - adds 7.5" to height
8.931-261.0	Pneumatic Tire Kit with Handle Bar (Field Installed) - adds 10" to width, 6" to height
8.916-175.0	High Pressure Detergent Kit, 1075BE & 1080BE models (to be used with a remote water tank)
8.916-174.0	High Pressure Detergent Kit, 965B models (to be used with a remote water tank)
8.915-274.0	Stainless Steel Coil Wrap (Field Installed)

1200 SERIES

and Model 5645

- Gas-Powered
- Oil-Fired
- Belt Drive
- Electric Start
- 7-Year Pump Warranty



1260SS



1270SS Shown with optional Portage Kit



5645

The **1200 Series** delivers some serious on-site, hot water cleaning capability of up to 6 GPM and 4000 PSI. Rugged gasoline engines all have electric start. Six models come with a 2000W generator. The self-contained cleaning units are built to hold up under the toughest of conditions. All feature the Hotsy Triplex pump, with its 7-year warranty and ETL safety certification (CSA-Certified for non-generator models). All 1200 Series models are equipped with a standard flow switch and 50' hose.



MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	BURNER	BTU/HR	PUMP MODEL	DRIVE	PORTABILITY	DIMENSIONS	SHIP WT (lbs)
1260SS	1.110-533.0	4.5	3000	Briggs VAN 16	479	12V DC	385,800	HHC506R.2	Belt	Optional	45"Lx33"Wx52"H	745
1260SSG*	1.110-535.0	4.5	3000	Briggs VAN 16	479	120V AC	398,400	HHC506R.2	Belt	Optional	45"Lx33"Wx52"H	830
1270SS	1.110-557.0	4.5	4000	Honda GX630	688	12V DC	385,800	HHC930R.1	Belt	Optional	45"Lx33"Wx52"H	855
1270SSG*	1.110-536.0	4.5	4000	Honda GX630	688	120V AC	398,400	HHC930R.1	Belt	Optional	45"Lx33"Wx52"H	870
1280SS	1.110-558.0	5.1	3500	Honda GX630	688	12V DC	385,800	HX8043R.2	Belt	Optional	45"Lx33"Wx52"H	760
1280SSG*	1.110-537.0	5.1	3500	Honda GX630	688	120V AC	398,400	HX8043R.2	Belt	Optional	45"Lx33"Wx52"H	750
1285SS	1.110-043.0	5.1	3500	Briggs VAN 21	627	12V DC	385,800	HX8043R.2	Belt	Optional	45"Lx33"Wx52"H	840
1285SSG*	1.110-044.0	5.1	3500	Briggs VAN 21	627	120V AC	398,400	HX8043R.2	Belt	Optional	45"Lx33"Wx52"H	895
1290SS	1.110-538.0	5.6	3000	Honda GX630	688	12V DC	385,800	HX8043R.2	Belt	Optional	45"Lx33"Wx52"H	744
1290SSG*	1.110-539.0	5.6	3000	Honda GX630	688	120V AC	398,400	HX8043R.2	Belt	Optional	45"Lx33"Wx52"H	905
5645*	1.110-556.0	6.0	3000	Honda GX660	688	120V AC	528,000	HX8043R.2	Belt	Optional	61"Lx32"Wx50"H	1126

* Models include a 2000W Generator 12V battery is required for all models, but is not supplied

SUPER DUTY OPTION KIT

PART NO.	DESCRIPTION
8.903-081.0	1285SS / 1285SSG

OPTION

PART NO.	DESCRIPTION
8.903-025.0	Portage Kit (all models except 5645)

General Description-Modifications to existing equipment (Super Duty Option):

Remove Float Tank. Replace Flow Switch with HD Pressure Switch. Replace unloader with VB80. Remove inlet detergent injector. Add Hot Seals to pump. Replace existing coil with stainless steel wrapped coil with base plate. Coil wound as a gas coil to reduce soot build up.

Super Skid HSS SERIES

- Diesel-Powered
- Oil-Fired
- Belt Drive
- Electric-Start
- 7-Year Pump Warranty



The Super Skid HSS Series is by far, the largest, most powerful of Hotsy's hot water pressure washers. All models come standard with the reliable Hotsy triplex belt-driven high-pressure pump. The Super Skid HSS series models are rated for continuous use and are ideal for heavy duty, on-site cleaning where electricity is not available. Models are powered by a Lombardini engine with electric start and all feature a 3/4-inch Schedule 80 heating coil with stainless steel skin and 5-year warranty. A flow switch is a standard feature on all HSS Super Skid models.



MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	BURNER	BTU/HR	PUMP MODEL	HOSE	DIMENSIONS	SHIP WT (lbs)	LIST PRICE
HSS-503089E	1.110-546.0	5.0	3000	Kohler KDW702	686	120V AC	620,000	HX5843R.2	50'-3/8"	66"Lx37"Wx53"H	1790	\$19,549
HSS-603289E	1.110-547.0	6.5	3200	Kohler KDW1003	1028	120V AC	620,000	HX5843R.2	50'-3/8"	66"Lx37"Wx53"H	1825	\$20,399
HSS-803089E	1.110-548.0	8.0	3000	Kohler KDW1003	1028	120V AC	744,000	HX5843R.2	50'-1/2"	73"Lx37"Wx64"H	2165	\$22,799
HSS-102589E	1.110-545.0	9.5	2500	Kohler KDW1003	1028	120V AC	920,000	HX1036R.2	50'-1/2"	73"Lx37"Wx64"H	2200	\$22,799

All Models are Electric Start and include a 2000W Generator. 12V battery is required for all models, but is not supplied

HWE SERIES

All Electric Models

- All Electric
- Belt Drive
- Auto/Start Stop
- Stainless Steel Coil
- 7-Year Pump Warranty



The HWE Series is powered and heated by electricity, making it ideal for indoor use. It's a quiet machine with no fumes, making it ideal for food service and in-plant cleaning. Water is heated in a stainless steel heating coil, immersed in a tank of water solution, allowing for instant hot water once you pull the trigger. The heating elements do not come in contact with the pressurized water, which results in less maintenance and minimizes scale build up. The HWE features a Baldor motor, which drives a belt-drive Hotsy Triplex pump, with 7-year warranty, and an insulated variable pressure wand. ETL certified. Flow switch is standard on the HWE Series. All models equipped with a 50' hose.



MODEL	PART NO.	GPM	PSI	HP	MOTOR	AMPS	VOLT / PH	KvA HOUR	BTU /	PUMP MODEL	DRIVE	DIMENSIONS	SHIP WT (lbs)
HWE-4020C	1.109-646.0	4.0	2000	6.2	Baldor	55.2	460/3	40.5	138,308	HH306R.2	Belt	34"Lx25"Wx52"H	620
HWE-4030C	1.109-647.0	3.5	3000	7.5	Baldor	59	460/3	40.5	138,308	HH306R.2	Belt	34"Lx25"Wx52"H	640

OPTIONS

PART NO.	ORIG NO.	DESCRIPTION
8.903-042.0	280711	Stainless Steel Washer Wrap 1700 Series (Factory installed)*
8.725-157.0	280730	Option, Time Delay Shutdown HWE-4020C (Factory installed)
8.725-158.0	280731	Option, Time Delay Shutdown HWE-4030C (Factory installed)

*Note: Stainless steel option for the heater cabinet (lower) is available through standard specials

9400 SERIES Heating Modules

The **9400 Series** heating modules give customers the flexibility to “convert” a cold water pressure washer into a hot water unit. By attaching the heating module to a cold water pressure washer the pressurized water is now heated to produce all the benefits of hot water cleaning. The four models use fuel oil, diesel or natural gas to heat the water using Hotsy’s high-efficiency, vertical heating coil. All models are equipped with a flow switch to control the burner.



Model 9462



Model 9452



MODEL	PART NO.	PSI (Max)	GPM (Max)	GPM (Min)	VOLT/PH	BTU/HOUR	AMP	FUEL	DIMENSIONS	SHIP WT (lbs)
9450	1.103-905.0	3200	10	6	115/1	700,000	8	Oil-Fired	32.5”Lx25”Wx50.5”H	525
9452	1.103-906.0	3200	10	6	115/1	540,000	1	Natural-Gas-Fired	32.5”Lx25”Wx50.5”H	500
9460	1.103-907.0	3200	10	6	115/1	920,000	8	Oil-Fired	40.5”Lx32”Wx65”H	920
9462	1.103-908.0	3200	10	6	115/1	920,000	1	Natural-Gas-Fired	40.5”Lx32”Wx65”H	935

OPTIONS

PART NO.	ORIG NO.	DESCRIPTION
8.903-076.0	480291	Natural-Gas to LP Conversion for Model 9452 (Factory Installed)
8.903-075.0	480290	Natural-Gas to LP Conversion for Model 9462 (Factory Installed)
9.801-040.0	835525	10” Natural Gas-Fired Draft Diverter for Model 9452
8.717-730.0	835531	12” Natural Gas-Fired Draft Diverter for Model 9462

Fuel-burner types available:

- Diesel ■ Kerosene ■ Home Heating Oil
- Natural Gas ■ LP Gas (Optional)

Trail Blazer TRAILER

- 200 Gallon Water Tank
- Single axle rated to 3500 pounds
- Swing away hinged tongue



Shown with 1080BE and optional accessories

The **Trail Blazer** is Hotsy’s affordable trailer solution that provides mobile cleaning anywhere. Axle assembly with leaf-spring suspension is rated at 3,500 lbs. The heavy duty-chassis features a swing-away hinge with swivel jack tongue assembly. The 200 gallon water tank features a float valve and 7-inch access port. 15-inch white spoke wheel assembly. Idler axle (no brakes) is the standard configuration.

Select a trailer and add one of these pressure washer models:

- 965B
- 1075BE
- 1075SSE
- 1080BE
- 1200 Series

MODEL	PART NO.	LOAD CAPACITY	WATER TANK CAPACITY	AXLE	WHEELS	JACK	JACK CAPACITY	BALL COUPLER	SAFETY CHAINS	LIGHTING
TRB-3500	1.103-818.0	3000 lbs	200 gal	Single 3500 lbs	15” White Spoke Wheels ST205/75D15 Tires	Swivel Wheel w/Caster Foot	1000 lbs	2”	Dual 5/16”	Recessed Lights are DOT approved

Trailer Dimensions 136” L x 66” W x 52” H

Trailer Weight: 543 lbs.

Shipping Weight: 1043 lbs. (does not include pressure washer)

OPTIONS (FACTORY INSTALLED)

PART NO.	DESCRIPTION
8.917-397.0	Brakes, Electric
8.917-398.0	Brakes, Hydraulic
8.917-553.0	Break-Away (available w/Electric Brakes)
8.917-554.0	High Pressure Hose Reel
8.917-555.0	Low Pressure Hose Reel
8.917-556.0	Saddle Box Kit, set of two
8.917-557.0	Rock Guard Kit
8.917-538.0	Chrome Wheel Rims

OPTIONS (FACTORY INSTALLED)

PART NO.	DESCRIPTION
8.917-290.0	Assembly Mounting (for 1200 Series)*
8.917-291.0	Assembly Mounting (for 965B, 1075BE, 1080BE Models)*
8.917-471.0	Assembly Mounting (for 1260SS/SSG Models)*
8.917-472.0	Assembly Mounting (for 1075SSE Model)*

*Required when purchasing a pressure washer and trailer package; NOT available for trailer purchases only

KITS (FIELD INSTALLED)

PART NO.	DESCRIPTION
8.917-559.0	Rock Guard Kit
8.917-558.0	Saddle Box Kit - single box only
8.917-560.0	Utility Rack Kit (150 lb. load capacity)

BD SERIES

BELT DRIVE

BD Series shown in large cage (4-wheel) version. Small cage 2-wheel version also available.



The **BD Series** is the most rugged cold water pressure washer on the market with its all-steel frame and cage, Hotsy belt-drive, triplex pump and cleaning power of up to 5000 PSI. Four gas models make up what is Hotsy's most durable cold water line-up ever. All models equipped with a 50' hose.



- Honda or Vanguard engine
- Small & Large Roll Cage design with lifetime warranty
- Totally enclosed belt guard
- 13" tubed pneumatic tires for easy handling
- Plated steel high-pressure wand w/ side handle
- ETL certified to UL-1776 safety standards

MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	PUMP MODEL	FRAME	DIMENSIONS	NO. WHEELS	SHIP WT (lbs)
BD-373539	1.107-021.0	3.7	3500	Honda GX390	389	HM4035R.2	Small Cage	42"Lx26"Wx30"H	2	275
BD-404029	1.107-022.0	4.0	4000	Briggs VAN 16	479	HHC930R.1	Large Cage	46"Lx30"Wx36"H	4	360
BD-405039E*	1.107-023.0	4.0	5000	Honda GX630	688	HH5050R	Large Cage	46"Lx30"Wx36"H	4	417
BD-455039E*	1.107-024.0	4.5	5000	Honda GX660	688	HH5050R	Large Cage	46"Lx30"Wx36"H	4	430
BD-343089E*	1.107-083.0	3.4	3000	Kohler KD420 Diesel	442	HM3540R.2	Large Cage	46"Lx30"Wx36"H	4	410

*E = Electric Start

OPTIONS		OPTIONS	
PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
8.904-109.0	E-Zee Hose Reel Kit*100' (small cage)	8.904-113.0	5000 PSI Hose Reel Kit* (large cage)
8.904-110.0	E-Zee Hose Reel Kit*100' (large cage)	8.904-115.0	5000 PSI Dual Hose Reel Kit,*† (large cage)

*Kit includes hose reel and mounting hardware †Includes garden hose reel and high-pressure hose reel

BX/BXA SERIES

BELT DRIVE



BX Series shown with optional hose reel & mounting kit.

The **BX/BXA Series** is the similarly rugged, but more compact, line of belt-drive cold water pressure washers. Powered by Honda engines, the BX/BXA series delivers cleaning power up to 3500 PSI and an all-steel frame protected by a durable powder coat finish. The Hotsy triplex pumps carry a 7-year warranty. Equipped with a 50' hose.

- Honda engines
- Steel & Aluminum frame
- Totally enclosed belt guard
- 13" tubed pneumatic tires for easy handling
- Insulated steel high-pressure wand w/ side handle
- ETL certified to UL-1776 safety standards

Note: Chemical Injector Sold Separately on BXA models



MODEL	PART NO.	GPM	PSI	ENGINE	CC's	START	PUMP MODEL	FRAME	DIMENSIONS	DRIVE	SHIP WT (lbs)
BX-282039	1.107-026.0	2.8	2000	Honda GX160	163	Recoil	HD3030R.1	Small Chassis	37"Lx21"Wx24"H	Belt	152
BX-373539	1.107-028.0	3.7	3500	Honda GX390	389	Recoil	HM4035R.2	Large Chassis	45"Lx26"Wx24"H	Belt	240
BXA-252739	1.107-120.0	2.5	2700	Honda GX200	196	Recoil	HD3030R.1	Aluminum	45.9"Lx26"Wx39.7"H	Belt	196
BXA-373539	1.107-121.0	3.7	3500	Honda GX390	389	Recoil	HM4035R.3	Aluminum	45.9"Lx27"Wx40.6"H	Belt	249

OPTIONS		OPTIONS	
PART NO.	DESCRIPTION	PART NO.	DESCRIPTION
8.929-062.0	Detergent Injector (up to 3 GPM)**	8.723-636.0	Detergent nozzle**
9.802-225.0	Detergent Injector (over 3 GPM)**	8.904-103.0	EZ Hose Reel Kit 100' (incl. reel & mounting hardware)*

** BXA models only

* BX models only

DB SERIES

DIRECT DRIVE

DB Series shown with optional hose reel & mounting kit.



The **DB Series** is the most compact, affordable alternative, in the cold water line featuring a direct-drive triplex pump. All four models are powered by reliable Honda engines. Light-weight design and tubed pneumatic tires make for easy maneuvering.



- Honda GX engines
- Steel frame with lifetime warranty
- 10" tubed pneumatic tires for easy handling
- Protected by a powder coat finish
- Insulated, 2-piece steel high-pressure wand
- ETL certified to UL-1776 safety standards

MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	PUMP MODEL	DRIVE	DIMENSIONS	HOSE	SHIP WT (lbs)
DB-232439	1.107-031.0	2.3	2400	Honda GX160	163	HG2530G.1	Direct	35"Lx21"Wx24"H	50'	130
DB-252739	1.107-032.0	2.5	2700	Honda GX200	196	HG2530G.1	Direct	35"Lx21"Wx24"H	50'	135
DB-303039	1.107-033.0	3.0	3000	Honda GX270	270	HG3035G1.1	Direct	35"Lx21"Wx24"H	50'	155
DB-383539	1.107-034.0	3.8	3500	Honda GX390	389	HS4040G.2	Direct	35"Lx21"Wx24"H	50'	185

OPTIONS	
PART NO.	DESCRIPTION
8.904-105.0	EZ Hose Reel Kit 100' (incl. reel & mounting hardware)

DBA SERIES

DIRECT DRIVE



The DBA Series are direct-drive cold water pressure washers with corrosion resistant aluminum frame, making them lightweight and easy to load and unload. Powered by Honda GX engines, the DBA series delivers cleaning power up to 3500 PSI. The commercial duty pump carry a 7-year warranty. Models equipped with a 50' hose.



- Honda GX engines
- Aluminum frame with fold down handle
- Thermal pump protector
- Tubed pneumatic tires for easy handling
- Hose and gun hanger for safe storage
- ETL certified to UL-1776 safety standards

Note: Chemical Injector Sold Separately

MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	START	PUMP MODEL	DRIVE	DIMENSIONS	HOSE	SHIP WT (lbs)
DBA-252739	1.107-117.0	2.5	2700	Honda GX200	196	Recoil	HG2530G.1	Direct	39.3"Lx22.5"Wx39.6"H	50'	125
DBA-303039	1.107-118.0	3.0	3000	Honda GX270	270	Recoil	HG3035G1.1	Direct	39.3"Lx22.5"Wx39.6"H	50'	148
DBA-383539	1.107-119.0	3.8	3500	Honda GX390	389	Recoil	HG4040G.2	Direct	40.8"Lx22.5"Wx39.6"H	50'	172

DA SERIES

DIRECT DRIVE



The DA Series is a rugged, yet compact, line of direct-drive cold water pressure washers. Powered by Honda GX or GC engines, the DA series delivers cleaning power up to 3500 PSI with an all-welded chassis protected with all-weather, epoxy powder coat finish. The Hotsy triplex pumps carry a 7-year warranty. 5 HP models equipped with a 25' hose; 6.5 & 13 HP models equipped with a 50' hose.



- Honda GX / GC engines
- All welded chassis
- Thermal pump protector
- Tubed pneumatic tires for easy handling
- Hose and gun hanger for safe storage
- ETL certified to UL-1776 safety standards

MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	START	PUMP MODEL	DRIVE	DIMENSIONS	HOSE	SHIP WT (lbs)
DA-232336	1.107-097.0	2.3	2300	Honda GC160	160	Recoil	COMET BXD	Direct	23"Lx22"Wx25"H	25'	73
DA-232337	1.107-098.0	2.3	2300	Honda GC160	160	Recoil	Legacy Axial	Direct	23"Lx22"Wx25"H	25'	90
DA-252739	1.107-100.0	2.5	2700	Honda GX200	196	Recoil	HG2530G1.1	Direct	23"Lx22"Wx25"H	50'	104
DA-383539	1.107-102.0	3.8	3500	Honda GX390	389	Recoil	HS4040G.2	Direct	36.5"Lx23.5"Wx30.5"H	50'	157

HAND-HELD COLD WATER PRESSURE WASHER - GAS ENGINE

HC SERIES

Gasoline-Powered

DIRECT DRIVE



The HC Series is the hand-held model of the gasoline-powered line, delivering cleaning capability up to 2400 PSI. The HC is driven by a Honda engine and features a reliable direct-drive triplex pump and is ETL safety certified.



- Honda engine
- Direct-drive high-pressure pump
- Cleaning power up to 2400 PSI
- Weighs 80 lbs.
- Lifetime warranty on frame
- Convenient carrying handle

MODEL	PART NO.	GPM	PSI	ENGINE / MODEL	CC's	PUMP MODEL	DRIVE	DIMENSIONS	HOSE	SHIP WT (lbs)
HC-232336	1.107-035.0	2.3	2300	Honda GC160	160	Legacy Axial	Direct	20"Lx16"Wx17"H	25'	74
HC-232439	1.107-036.0	2.3	2400	Honda GX160	163	HG2530G.1	Direct	20"Lx16"Wx17"H	25'	95

1700 SERIES

BELT DRIVE



Shown with optional stainless steel cabinet



The **1700 Series** offers the most reliable stationary, electric-powered, cold water pressure washer featuring a Hotsy belt-drive, triplex pump with 7-year warranty, insulated variable pressure wand and ETL safety certification. All models equipped with a 50' hose.

- Baldor electric motor, 2-10 HP
- Hotsy pump with 7-year warranty
- Downstream detergent injector
- Insulated SS variable pressure wand
- Hot Water Seal Kit standard
- Option-ready for time delay shutdown or automatic stop-start.

MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	AMPS	PUMP MODEL	DRIVE	PORTABILITY	DIMENSIONS	SHIP WT (lbs)
1710	1.106-511.0	2.75	1000	2	120/1	20	HD3030R.1	Belt	Optional	31"Lx21"Wx16"H	200
1720	1.106-512.0	3.9	2000	6	230/1	28	HH306R.2	Belt	Optional	31"Lx21"Wx16"H	275
1722	1.106-513.0	3.9	2000	6	208/1	30	HH306R.2	Belt	Optional	31"Lx21"Wx16"H	240
1723	1.106-514.0	3.9	2000	6	208/3	16	HH306R.2	Belt	Optional	31"Lx21"Wx16"H	250
1724	1.106-515.0	3.9	2000	6	230/3	14.4	HH306R.2	Belt	Optional	31"Lx21"Wx16"H	250
1725	1.106-516.0	3.9	2000	6	460/3	7.2	HH306R.2	Belt	Optional	31"Lx21"Wx16"H	250
1743	1.106-529.0	4.76	3000	10	208/3	31.3	HHC506R.2	Belt	Optional	31"Lx21"Wx16"H	302
1744	1.106-530.0	4.76	3000	10	230/3	26.8	HHC506R.2	Belt	Optional	31"Lx21"Wx16"H	300
1745	1.106-531.0	4.76	3000	10	460/3	13.5	HHC506R.2	Belt	Optional	31"Lx21"Wx16"H	315
1753	1.106-534.0	5.93	2500	10	208/3	31.3	HHC950R.1	Belt	Optional	31"Lx21"Wx16"H	320
1754	1.106-535.0	5.93	2500	10	230/3	26.8	HHC950R.1	Belt	Optional	31"Lx21"Wx16"H	310
1755	1.106-536.0	5.93	2500	10	460/3	13.5	HHC950R.1	Belt	Optional	31"Lx21"Wx16"H	310

OPTIONS	1700 SERIES
PART NO.	DESCRIPTION
9.801-031.0	Kit, 1700 Wheel w/Chemical Rack
9.801-033.0	Kit, 1700 Wall Mount
9.801-034.0	Kit, 1700 Floor Stand, Tall (20 3/4"W x 29"D x 36"H)
9.801-035.0	Kit, Caster Wheels for 1700 Floor Stand
8.903-039.0	Kit, Hose Reel w/Bracket for 1700 Stand & Wall Mount Kits
8.903-040.0	Kit, 1700 Floor Stand, Short (20 3/4"W x 29"D x 24"H)
8.903-043.0	Kit, 1700 Wall Mount, Stainless Steel
8.903-041.0	Time Delay Shut Down, For 172x, 173x & 174x Models (Factory Installed)
8.903-045.0	Time Delay Shut Down for 1710 (Factory Installed)
8.903-044.0	Time Delay Shut Down for 175x Models (Factory Installed)
8.903-042.0	Stainless Steel Base & Cover, 1700 Series (Factory Installed)
8.903-047.0	Automatic Stop/Start for 1710 & 172x Models (Factory Installed)
8.903-048.0	Automatic Stop/Start for 175x Models (Factory Installed)
8.903-046.0	Automatic Stop/Start for 173x & 174x Models (Factory Installed)
8.903-617.0	Kit, 1700 Floor Stand, Tall, Stainless Steel
8.903-521.0	Kit, Hose Reel for Wheel Kit 100 ft. (excludes hose)



Model 1710 shown with optional wheel kit (PN 9.801-031.0).



1700 Series shown with optional hose reel kit, (PN 8.903-039.0), cart (PN 9.801-034.0), caster wheel kit (PN 9.801-035.0) and stainless steel base and cover (PN 8.903-042.0).

BDE SERIES

BELT DRIVE



The **BDE Series** is the electric equivalent of the BD Series. Hotsy belt-drive, triplex pump and cleaning power of 5000 PSI. Both models feature the large cage frame and are equipped with a 50' hose.



- 1750 RPM Motor
- Totally enclosed belt guard
- 12' cord length
- NEMA 4-Electrical Box
- 13" tubed pneumatic tires for easy handling
- Plated steel high-pressure wand w/ side handle
- ETL certified to UL-1776 safety standards

MODEL	PART NO.	GPM	PSI	HP	MOTOR RPM	VOLTS	AMPS	PUMP MODEL	PUMP RPM	HOSE	DIMENSIONS	SHIP WT (lbs)
BDE-505009B	1.107-085.0	5.0	5000	20	1750	230 / 3	48	HH5050R	1650	50'	46"Lx30"Wx36"H	524
BDE-505009C	1.107-086.0	5.0	5000	20	1750	460 / 3	26	HH5050R	1650	50'	46"Lx30"Wx36"H	524

OPTIONS

PART NO.	DESCRIPTION
8.904-110.0	E-Zee Hose Reel Kit*100' (large cage)

OPTIONS

PART NO.	DESCRIPTION
8.904-113.0	5000 PSI Hose Reel Kit* (large cage)
8.904-115.0	5000 PSI Dual Hose Reel Kit,*† (large cage)

*Kit includes hose reel and mounting hardware †Includes garden hose reel and high-pressure hose reel

EP SERIES

DIRECT DRIVE



The **EP Series** offers a portable alternative to the electric-powered, cold water pressure washer line featuring the Hotsy direct-drive pump with a 7-year warranty. The EP's functional design is further enhanced by 10" tubed pneumatic tires, a convenient hose-and-gun rack and ETL safety certification.



- 1725 RPM Baldor electric motor
- Steel frame with lifetime warranty
- Hotsy pump with 7-year warranty
- Insulated wand and fatigue-free gun
- Powder coat finish protection
- ETL safety certification

MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	AMPS	PUMP MODEL	DRIVE	DIMENSIONS	HOSE	SHIP WT (lbs)
EP-201009D	1.106-025.0	2.0	1000	1.5	120/1	15	HE2020S.1	Direct	35"Lx21"Wx24"H	50'	151
EP-301009D	1.106-026.0	3.0	1000	2	120/1	20	HE2825S.1	Direct	35"Lx21"Wx24"H	50'	150
EP-301509A	1.106-027.0	3.0	1500	3	230/1	15	HE2825S.1	Direct	35"Lx21"Wx24"H	50'	157
EP-352009A	1.106-028.0	3.5	2000	5	230/1	20	HHC456R.1	Direct	35"Lx21"Wx24"H	50'	205

OPTIONS EP SERIES

PART NO.	DESCRIPTION
8.904-107.0	EZ Hose Reel Kit 100' (incl. reel & mounting hardware)

HAND-HELD COLD WATER PRESSURE WASHER - ELECTRIC

ET SERIES

Electric-Powered

DIRECT DRIVE



The **ET Series** is the hand-held model of the electric-powered line, delivering cleaning capability of 1400 PSI. The ET features a reliable direct-drive triplex pump and is ETL safety certified.



- 1725 RPM Motor
- Direct-drive high-pressure pump
- 25' hose
- Remote switch with 6' cord
- Accepts incoming hot water up to 180°F
- Convenient carrying handle
- Standard auto start/stop

MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	PUMP MODEL	DRIVE	DIMENSIONS	HOSE	SHIP WT (lbs)
ET-201409DX2	1.107-089.0	1.8	1400	2.0	115/1	HE2020S	Direct	20"Lx19"Wx17"H	25'	123

OPTIONS ET SERIES

PART NO.	DESCRIPTION
8.920-952.0	Wall Mount Bracket